

ALLBÄCK LINSEED OIL PRODUCTS

Distributed in the UK by



SWEDISH LINSEED PAINT

The rediscovery of ancient wisdom

www.swedishlinseedpaint.co.uk

info@swedishlinseedpaint.co.uk

LINSEED OIL WAX

(See also the Allback Concise Handbook and Videos on our website)

Linseed oil wax is made from linseed oil and bees wax. The wax is used as a surface protector on unpainted, varnished or painted wooden surfaces. The wax is easy to apply with a sponge or cloth. The surface should be clean and dry.

- Ideal for protecting exterior hardwoods.
- 1 litre of wax should cover 20 square metres.

Instructions for Softwood and Hardwood Floorboards, Furniture and Doors

Suitable for use on timber floors and work surfaces, furniture, garden furniture, wooden decks, windows and doors, where a bare wood finish is preferred.

1. Clean the wooden surface with Linseed Oil Soap or brush/sand away loose particles.
2. Warm Raw Linseed Oil to approximately 60°C, apply one coat to the timber. Allow to dry thoroughly – 24 to 48 hours.
3. Apply a coat of Linseed Oil Wax using a lint free cloth¹, sponge or brush, working it into the surface as you go. This will be facilitated if you apply heat at the same time from a heat gun (not too hot) or a hairdryer.
4. A couple of hours after application please polish using a soft cloth².
5. A second coat of wax may then be applied. Leave at least a fortnight before applying this coat, to give the Linseed Wax time to cure properly. Again, wait a couple of hours before polishing. (Floorboards can be walked on between coats). Footprints and other marks in the wax that now appear will disappear by themselves.

Maintenance: Further coats of Linseed Oil Wax will be required approximately every two to four years for external surfaces (depending on aspect), and more frequently for floorboards (depending on footfall). Future coats of wax can be applied over the top of existing coats (we would recommend that the timber is cleaned first) and polished in the same manner as above. Mops and spills should be sponged off the surface. Clean floors periodically (not too frequently) with approximately one teaspoon of Linseed Oil Soap in a bucketful of hot water.

¹ Cloths and rags soaked in linseed oil can spontaneously combust. Please soak in water before disposal in outside waste.